

ACCESORIOS DE POLIETILENO INYECTADO

Reducción inyectada



Con cuello largo para soldar con manguitos.

Máxima presión de trabajo permitida: 16 bar(agua) / 10 bar (gas).



Código	Referencia	d1 / d2	P.V.P./€
ft-1001101	RDE 32-20	32-20	3,10
ft -1001102	RDE 32-25	32-25	3,44
ft -1001103	RDE 40-20	40-20	5,04
ft -1001104	RDE 40-25	40-25	5,04
ft -1001105	RDE 40-32	40-32	4,06
ft -1001106	RDE 50-25	50-25	5,36
ft -1001107	RDE 50-32	50-32	5,90
ft -1001108	RDE 50-40	50-40	5,90
ft -1001109	RDE 63-32	63-32	4,90
ft -1001110	RDE 63-40	63-40	5,18
ft -1001111	RDE 63-50	63-50	7,22
ft -1001114	RDE 90-50	90-50	17,10
ft -1001115	RDE 90-63	90-63	16,48
ft -1001117	RDE 110-63	110-63	15,64
ft -1001119	RDE 110-90	110-90	18,70
ft -1001120	RDE 125-63	125-63	18,70
ft -1001122	RDE 125-90	125-90	27,32
ft -1001123	RDE 125-110	125-110	25,92
ft -1001126	RDE 160-110	160-110	52,82
ft -1001127	RDE 160-125	160-125	52,82
ft -1001132	RDE 200-160	200-160	75,60
ft -1001141	RDE 315-250	315-250	240,58

Codo 45° inyectado



Con cuello largo para soldar con manguitos.

Máxima presión de trabajo permitida: 16 bar(agua) / 10 bar (gas).



Código	Referencia	diámetro	P.V.P./€
ft-1101101	HDE 20	20	4,84
ft-1101102	HDE 25	25	5,04
ft-1101103	HDE 32	32	4,80
ft-1101104	HDE 40	40	6,46
ft-1101105	HDE 50	50	8,44
ft-1101106	HDE 63	63	9,10
ft-1101107	HDE 75	75	20,18
ft-1101108	HDE 90	90	17,54
ft-1101109	HDE 110	110	25,58
ft-1101110	HDE 125	125	33,30
ft-1101111	HDE 140	140	74,82
ft-1101112	HDE 160	160	65,62
ft-1101113	HDE 180	180	75,78
ft-1101114	HDE 200	200	102,94
ft-1101115	HDE 225	225	131,46
ft-1101116	HDE 250	250	209,70
ft-1101118	HDE 315	315	335,72



Codo 90° inyectado



Con cuello largo para soldar con manguitos.

Máxima presión de trabajo permitida: 16 bar(agua) / 10 bar (gas).



Código	Referencia	diámetro	P.V.P./€
ft-1201101	GDE 20	20	4,42
ft-1201102	GDE 25	25	3,98
ft-1201103	GDE 32	32	2,26
ft-1201104	GDE 40	40	6,34
ft-1201105	GDE 50	50	8,44
ft-1201106	GDE 63	63	10,08
ft-1201107	GDE 75	75	19,82
ft-1201108	GDE 90	90	15,08
ft-1201109	GDE 110	110	21,16
ft-1201110	GDE 125	125	30,88
ft-1201111	GDE 140	140	69,46
ft-1201112	GDE 160	160	77,52
ft-1201113	GDE 180	180	99,20
ft-1201114	GDE 200	200	130,36
ft-1201115	GDE 225	225	179,66
ft-1201116	GDE 250	250	321,12
ft-1201118	GDE 315	315	615,12

TE igual 90° inyectada



Con cuello largo para soldar con manguitos.

Máxima presión de trabajo permitida: 16 bar(agua) / 10 bar (gas).



Código	Referencia	diámetro	P.V.P./€
ft-1301101	TDE 20	20	3,34
ft-1301102	TDE 25	25	5,52
ft-1301103	TDE 32	32	3,62
ft-1301104	TDE 40	40	5,04
ft-1301105	TDE 50	50	10,64
ft-1301106	TDE 63	63	9,08
ft-1301107	TDE 75	75	22,06
ft-1301108	TDE 90	90	21,26
ft-1301109	TDE 110	110	29,78
ft-1301110	TDE 125	125	43,56
ft-1301111	TDE 140	140	117,66
ft-1301112	TDE 160	160	96,78
ft-1301113	TDE 180	180	182,56
ft-1301114	TDE 200	200	149,64
ft-1301115	TDE 225	225	206,30
ft-1301116	TDE 250	250	286,04
ft-1301118	TDE 315	315	669,38

Tapón – Cap inyectado



Con cuello largo para soldar con manguitos.

Máxima presión de trabajo permitida: 16 bar(agua) / 10 bar (gas).



Código	Referencia	diámetro	P.V.P./€
ft-1401101	CDE 20	20	2,14
ft-1401102	CDE 25	25	2,14
ft-1401103	CDE 32	32	2,26
ft-1401104	CDE 40	40	2,52
ft-1401105	CDE 50	50	7,84
ft-1401106	CDE 63	63	6,66
ft-1401107	CDE 75	75	21,10
ft-1401108	CDE 90	90	16,34
ft-1401109	CDE 110	110	25,24
ft-1401110	CDE 125	125	28,78
ft-1401111	CDE 140	140	40,48
ft-1401112	CDE 160	160	40,12
ft-1401113	CDE 180	180	58,74
ft-1401114	CDE 200	200	99,36
ft-1401115	CDE 225	225	118,82
ft-1401116	CDE 250	250	136,88
ft-1401118	CDE 315	315	192,88

Portabridas inyectado



Con cuello largo para soldar con manguitos.

Máxima presión de trabajo permitida: 16 bar(agua) / 10 bar (gas).



Código	Referencia	diámetro	P.V.P./€
ft-1501101	QDE 20	20	4,18
ft-1501102	QDE 25	25	4,14
ft-1501103	QDE 32	32	4,82
ft-1501104	QDE 40	40	5,72
ft-1501105	QDE 50	50	7,34
ft-1501106	QDE 63	63	8,62
ft-1501107	QDE 75	75	10,82
ft-1501108	QDE 90	90	9,46
ft-1501109	QDE 110	110	12,54
ft-1501110	QDE 125	125	18,10
ft-1501111	QDE 140	140	28,22
ft-1501112	QDE 160	160	22,78
ft-1501113	QDE 180	180	28,80
ft-1501114	QDE 200	200	57,96
ft-1501115	QDE 225	225	62,28
ft-1501116	QDE 250	250	95,72
ft-1501118	CDE 315	315	160,58

Brida de acero

Recubierta de PP DIN2501 – PN10.



Código	Referencia	DN	P.V.P./€
ft-0000002	QDM 20	20	7,10
ft-0000003	QDM 25	25	10,88
ft-0000004	QDM 32	32	12,02
ft-0000005	QDM 40	40	14,34
ft-0000006	QDM 50	50	21,80
ft-0000007	QDM 65	65	23,84
ft-0000008	QDM 80	80	28,88
ft-0000009	QDM 100	100	36,24
ft-0000010	QDM 125	125	31,06
ft-0000011	QDM 150	150	49,28
ft-0000015	QDM 200	200	71,92
ft-0000016	QDM 250	250	89,86
ft-0000018	QDM 300	300	139,46

TRANSICIONES MONOBLOCK

Transiciones Acero/PE y Cobre/PE fabricadas según UNE 60.405-2.



Código	Referencia	P.V.P./€
acp-1001	Transición Ac 1" PE 32	18,80
acp-1002	Transición Ac 1 1/4" PE 40	25,36
acp-1003	Transición Ac 2" PE 63	40,22
acp-1004	Transición Ac 3" PE 90	67,62
acp-10041	Transición Ac 4" PE 110	137,98
acp-1005	Transición Ac 6" PE 160	182,14
acp-1006	Transición Cu 15x18 PE 20	19,24
acp-1007	Transición Cu 19x22 PE 32	24,92
acp-1008	Transición Cu 39x42 PE 40	41,98
acp-1009	Transición Cu 51x54 PE 63	58,62