

VASOS DE EXPANSION

Vasos de expansión calefacción

Certificación: PED- 97/ 23/ CE.
Temperatura máx. de trabajo: 99°C.

Membrana Fija

Presión máxima de ejercicio: 8 bar.
Presión de precarga: 1,5 bar.



Código	Modelo	Capacidad lts	D.ext. (mm)	Altura (mm)	Conex. Ø	P.V.P./€
VE-0005	ER- 5	5	205	225	3/4" M	22,60
VE-0008	ER- 8 CE	8	205	300	3/4" M	23,66
VE-0012	ER-12 CE	12	270	300	3/4" M	26,36
VE-0018	ER- 18 CE	18	270	410	3/4" M	29,44
VE-0024	ER- 24 CE	24	320	355	3/4" M	36,02

Membrana Fija

Presión máxima de ejercicio: 10 bar
Presión de precarga: 1,5 bar.



Código	Modelo	Capacidad lts	D.ext. (mm)	Altura (mm)	Conex. Ø	P.V.P./€
VE-0035	ERCE- 35	35	400	390	3/4" M	52,70
VE-0050	ERCE- 50	50	400	500	1" M	72,04
VE-0050P	ERCE- 50/P	50	400	598	1" M	77,26
VE-0080	ERCE- 80	80	400	840	1" M	113,98
VE-0100	ERCE- 100	100	500	795	1" M	149,46
VE-0150	ERCE- 150	150	500	1025	1" M	197,84
VE-0200	ERCE- 200	200	600	1100	1" M	257,56
VE-0250	ERCE- 250	250	650	1190	1" M	332,58
VE-0300	ERCE- 300	300	650	1265	1" M	375,00
VE-0500	ERCE- 500	500	775	1423	1 1/4" M	564,38

Membrana Recambiable

Presión máx. de ejercicio: 10 bar.
Se suministra sin precarga, excepto AFV-500 CE (1,5 bar)



Código	Modelo	Capacidad lts	D.ext. (mm)	Altura (mm)	Conex. Ø	P.V.P./€
AA-0500V	AFV- 500 CE	500	775	1423	11/4" M	715,84
VEL-0750	ERL- 750 CE	750	800	1960	2" M	1.693,04
VEL-1000	ERL- 1000 CE	1000	800	2340	2" M	2.554,40
VEL-2000	ERL- 2000 CE	2000	1100	2750	DN80/ PN40	8.465,16
VEL-3000	ERL- 3000 CE	3000	1250	3100	DN80/ PN40	10.246,86
VEL-5000	ERL- 5000 CE	5000	1550	1960	DN80/ PN40	12,550,82